

# BHARAT DEEP

Genset, Diesel Engine & Pump Set



**E**xtrême  
**E**ngineering

# GENERATING SETS




## MINI AIR COOLED GENSET SINGLE CYLINDER, HT TYPE

- Single Phase, 220V, 1500 RPM, 50 Hz
- Range 2.5 KVA & 3.0 KVA
- Portable Genset with Resistive Alternator
- Self Start

## AIR COOLED GENSET SINGLE CYLINDER

- Single Phase, 220V, 1500 RPM, 50 Hz
- Range 2.5 KVA & 7.5 KVA
- Three Phase, 415V, 1500 RPM, 50 Hz
- Range 7.5 KVA & 8.7 KVA
- with Resistive/ Inductive type Alternator




## AIR COOLED GENSET DOUBLE CYLINDER

- Single Phase, 220V, 1500 RPM, 50 Hz
- Range 10.5 KVA & 12.0 KVA
- Three Phase, 415V, 1500 RPM, 50 Hz
- Range 12.5 KVA & 15 KVA
- with Resistive/ Inductive type Alternator

## WATER COOLED GENSET SINGLE CYLINDER

- Single Phase, 220V, 1500 RPM, 50 Hz
- Range 2.5 KVA & 10 KVA
- Three Phase, 415V, 1500 RPM, 50 Hz
- Range 7.5 KVA & 12.5 KVA
- with Resistive/ Inductive type Alternator



## WATER COOLED GENSET DOUBLE CYLINDER

- Single Phase, 220V, 1500 RPM, 50 Hz
- Range 2.5 KVA & 7.5 KVA
- Three Phase, 415V, 1500 RPM, 50 Hz
- Range 7.5 KVA & 8.7 KVA
- with Resistive/ Inductive type Alternator

# AC & DC WELDING SETS

## WATER COOL WELDING SET SINGLE CYLINDER

- A.C. Current, Semi Brush-less Technology (Rotation Field)
- Range 220, 250 & 270 Amp.
- Un-interrupted ARC Welding
- Optional Single Phase Light ( 2.5 KVA to 5.0 KVA at 220 V )
- Low Diesel Consumption Design.



## DIESEL PUMPSET

### TECHNICAL SPECIFICATION

Model	Rated Power HP	KW	R.P.M	NO OF CYL	BORE (mm) x STROKE (mm)	Dry Weight
Jl-9	5	3.7	1500	1	80 x 110	140
Jl-1	6.5	4.8	1500	1	85 x 110	145
Jl-2	7.5	5.5	1500	1	87.5 x 110	150
Jl-4	8	5.9	1600	1	87.5 x 110	155
Jl-5	10	7.36	1500	1	95 x 115	165
Jl-6	12	8.8	1600	1	102 x 115	170
Jl-7	14	10.3	1500	1	114.3 x 115	180



## ALTERNATORS ("INDOGEN" SERIES)

- Single Phase (5 KVA to 36 KVA) Three Phase (15 KVA to 42.5 KVA)
- Drip Proof, Self Excited, Screen Protected, Revolving Field, Class F Insulation, Great Efficiency (Appx. 90%)
- Alternator Specifications as per IS : 13364

## WELDING ALTERNATORS

- Range - 220 to 300 Amp
- Dual Function welding and Single Phase Load (2.5 KVA to 5.0 KVA)
- Smooth welding Control
- High Efficiency Design



Export in  
**MULTIPLE COUNTRIES**



**JYOTI INDUSTRIES**

Near Ganga Dharam Kanta, Opp. Mandi Samiti, Firozabad Rd, Agra-6 (U.P.) India  
Email : [jyotiindustries25@gmail.com](mailto:jyotiindustries25@gmail.com), Website : [www.jyoti-industries.in](http://www.jyoti-industries.in)

